

BALLISTOL CYLINDER SPRAY

Product Features

Special oil for lubricating and cleaning all kinds of locking cylinders and locks

Special Features

- Contains ceramic particles
- Maintaining, protecting and water displacing
- Reduces friction, part remains smoothly operating
- No more squeaking and creaking
- Displaces moisture and therefore also prevents icing up
- Guarantees lifelong perfect function
- Protects against corrosion and dissolves any existing corrosion
- PTFE and silicone-free

Application / Practical Tips

- For locking cylinders and locks of all types
- For precise application, attach the enclosed capillary tube
- Locks pre-treated with graphite should not be treated with oil - please follow the manufacturer's instructions



Available as	art.no.
50 ml	25940
50 ml cardboard blister	25941

Physical and Chemical Characteristics

- Appearance: light yellow
- Odour: characteristic
- Flash Point: approx. -104 °C (propane)
- Boiling Point: -48 °C (propane)
- Lower Explosion Limit: approx. 1.5 Vol-% (propane)
- Upper Explosion Limit: 10.9 Vol-% (propane)
- Relative Density: approx. 0.9 g/ml (in liquid phase)
- Viscosity Kinematic: approx. 28 (in liquid phase)

Hazard Statement

- Extremely flammable aerosol.
- Pressurised container: May burst if heated.

Important Product Advantages

- Practical product size
- Reduces friction
- Optional capillary tube
- Reaches even the tightest gaps
- With ceramic particles
- No more squeaking and creaking
- Maintaining, protecting and water displacing
- Displaces moisture
- Therefore also prevents icing up
- Parts remain smoothly operating
- PTFE- and silicone-free



Other products among BALLISTOL's technical products

- Premium Rust Protection Oil
- Multifunctional Garage Oil
- Copper Graphite Spray
- Silicone Oil
- Grinding Oil



BALLISTOL GmbH
Ballistolweg 1
D-84168 Aham
Tel. +49 (0) 8744 9699-0
Fax +49 (0) 8744 9699-99
info@ballistol.de
www.ballistol.de/shop/en