

Product information



IT WORKS.

BALLISTOL MULTI-PURPOSE GREASE

Product Features

Lithium soap grease for long-term lubrication according to DIN 51825: KP 2 K-30 and ISO 6743-9: ISO-L-XCCHB 2

Special Features

- Reduces friction and abrasion
- Protects against corrosion
- Big temperature application range, high drop point
- Very high water resistance, water displacing
- Provides good sealing
- High pressureload-carrying ability, high mechanical load capacity
- Resistant to aging

Application / Practical Tips

- For use as plain and roller bearing lubrication
- Easy to pump in central lubrication systems
- Resistant in dusty and wet environments as well as cold and hot water



Available as	art.no.
400 g	25350
1 kg	25351
5 kg	25352

Physical and Chemical Characteristics

- Appearance: paste-like, brownish, smooth
- Odour: characteristic
- Relative Density: approx. 0.9 g/cm³
- Viscosity (40 °C): 100 mm²/s (ASTM D 7042)
- Temperature application range: -35 °C to 130 °C
- Drop point: 190 °C (DIN ISO 2176)
- Pourpoint: approx. -30 °C
- Fulling penetration (0.1 mm, 60 double strokes): 280 (DIN ISO 2137)
- Fulling penetration (0.1 mm, 10 000 double strokes): 295 (DIN ISO 2137)
- NLGI class: 2 (DIN 51 818)
- Water resistance: Evaluation level 1 (DIN 51807-1)

Hazard Statement

/

Important Product Advantages

- Conformity with DIN and ISO standards
- High quality EP additive
- Reduces friction and wear
- Protects against corrosion
- Does not resinify
- Long-term lubrication
- Resistant in dusty and wet environments
- Resistant to cold and hot water
- Free of silicone, PTFE and acids



Other products among BALLISTOL's technical products

- Premium Rust Protection Oil
- Fine Mechanical Oil
- Multifunctional Garage Oil
- Copper Graphite Spray
- Silicone Oil



BALLISTOL GmbH
Ballistolweg 1
D-84168 Aham
Tel. +49 (0) 8744 9699-0
Fax +49 (0) 8744 9699-99
info@ballistol.de
www.ballistol.de/shop/en