

Product information



IT WORKS.

BALLISTOL WOOD GLIDE SPRAY

Product Features

Dry lubrication for application on degreased machine tables, sliding and adjusting devices

Special Features

Pure dry lubrication that prevents dirt from neither adhering nor being attracted to it

Leaves a dry and residue-free film

Wood to be worked thus glides easily over the machine table

Application / Practical Tips

Shake well before use

Spray onto the surfaces and parts to be treated at a distance of 10-25 cm and allow to dry for a few minutes

Suitable for easy, quick and safe application, even under machine operation

Subsequent treatment with stain, oil or varnish is not affected by the product

Also prevents whistling of wooden drills



Available as
Spray 400 ml

art.no.
25363

Physical and Chemical Characteristics

Appearance: colourless, clear

Odour: alcohol-like

pH value: approx. 7.5 (at 20 °C) – neutral

Flash Point: approx. -104 °C (propane)

Boiling Point: approx. 78 °C

Vapour Pressure: approx. 60 hPa (at 20 °C)

Relative Density: approx. 0.82 g/cm³ (at 20 °C, regarding liquid phase)

Lower Explosion Limit: 1.5 vol-% (propane)

Upper Explosion Limit: 10.9 vol-% (propane)

Solubility in Water: freely miscible

Temperature Application Range: -50 °C to 270 °C

Hazard Statement

Extremely flammable aerosol. Pressurised container:
May burst if heated. Causes serious eye irritation.

Important Product Advantages

- Contains biodegradable solvent
- Free of environmentally toxic substances
- Graphite and silicone free
- Residue-free
- High sliding activity
- Can be used in machine operation
- Also prevents whistling of wood drills



Other products among BALLISTOL's technical products

Premium Rust Protection Oil
Multifunctional Garage Oil
Copper Graphite Spray
Silicone Oil
Grinding Oil



BALLISTOL GmbH
Ballistolweg 1
D-84168 Aham
Tel. +49 (0) 8744 9699-0
Fax +49 (0) 8744 9699-99
info@ballistol.de
www.ballistol.de/shop/en