Product information

BALLISTOL PREMIUM RUST PROTECTION OIL

Product Features

For lubrication during thread cutting and for loosening tight screw connections and joints

Special Features

Cleans, protects and lubricates

Without waxes and silicones

Displaces moisture, prevents leakage currents

Eliminates squeaks and creaks

Prevents corrosion and freezing of door locks

Best preservation even in high humidity and aggressive ambient air

Application / Practical Tips

For maintenance and protection of machines, equipment, precision tools, measuring instruments, moulds and punches

Ideal for long-term preservation or intermediate storage of semi-finished and finished parts made of steel and iron inside or outside

Used in industry, crafts, vehicles of all kinds, shipping industry, agriculture, household and garden as well as fishing equipment



Available as	art.no.
Spray 200 ml	25260
Spray 400 ml	25261
5 liters	25264

Physical and Chemical Characteristics

Appearance: oil dark brown, spray light yellow Odour: oil mineral oil-like, spray characteristic pH value: oil not determined, spray approx. 8 (emulsion in water) Pour point: oil approx. -42 °C, spray not determined Flash point: oil > 62 °C, spray approx. -104 °C Lower explosion limit: oil not determined, spray approx. 1.5 vol-

Upper explosion limit: oil not determined, spray 10.9 Vol-% Vapor pressure: oil < 5 hPa, spray not determined Relative density: oil approx. 0.88 g/cm³, spray approx. 0.874 g/ml Viscosity kinematic: approx. 20 mm²/s, spray approx. 18 mm²/s Temperature application range: -40 °C to approx. +150 °C Refractive index: 1.48 (20°C)

Hazard Statement

Spray: Extremely flammable aerosol. Pressurised container: May burst if heated. Harmful to aquatic life with long lasting effects.

Liquid: Causes skin irritation. Causes serious eye irritation. Harmful to aquatic life with long lasting effects.

Important Product Advantages

- → Long-time protection from corrosion
- → Displaces moisture
- → Eliminates squeaks and creaks
- → Neutral towards rubber and plastics
- → Contact spray and rust remover
- → Does not contain animal oils
- → Does not resinify
- → Extremely wide range of application: in industry, craft, household, vehicles, agriculture, etc.
- → Does not contain silicones, PTFE, waxes or acids



Other products among BALLISTOL's technical products

Ballistol Universal Oil Multifunctional Garage Oil Multi-Purpose Grease Silicone Oil Fine Mechanical Oil





BALLISTOL GmbH Ballistolweg 1 D-84168 Aham Tel. +49 (0) 8744 9699-0 Fax +49 (0) 8744 9699-99 info@ballistol.de www.ballistol.de/shop/en